



STRAIGHT TO JOIST

dB Panel 37 has been designed as a versatile and high performing acoustic product to be used in conjunction with timber structures.

The unique combination of Eco-Friendly acoustic felt and rubber barrier matting make the product perform to all UK Building Regulations whether this be Approved Document E (England & Wales), Section 5 (Scotland) or Part G (Northern Ireland). dB Panel 37 can be laid in a overlay or straight to joist application. The unique composition of dB Panel 37 makes it very easy to install and quick to use.



Impact Rating **48 dB** L_{nTw}



Airborne Rating **56 dB** $D_{nTw} + C_{tr}$



Thickness **37mm**



Sheet Dimensions **2.4m x 0.6m**



Area **1.44m²**

All test data is site test data with suitable ceiling treatments & flanking paths removed. For more construction details for the test results please contact the office.

FEATURES

- ✓ Versatile and economical
- ✓ Suitable for New Build and Refurbishment Projects
- ✓ Compatible with a range of dB Systems
- ✓ Building Regulations Part E (England and Wales), Section 5 (Scotland) and Part G (Northern Ireland)
- ✓ Can achieve Robust Details Performance levels on timber frame development
- ✓ Easy to install in a single time saving operation
- ✓ A peel clean version is now available to allow for spotless handovers

SUITABLE FOR USE IN



HOME



WORK



LEISURE



EDUCATION



HEALTH

Telephone 01928 571 856
Email hello@soundinsulationstore.co.uk

www.soundinsulationstore.co.uk

Sound Insulation Store
Unit 4 Boleyn Court,
Manor Park Industrial Estate
Runcorn, WA7 1SR